



Tilting circular saw

Wisa 700Z and Wisa 700ZMG

The types Wisa 700Z and Wisa 700ZMG are user friendly and secure solutions for working with wood in agriculture and forestry.

They are very easy to use and have a clear and simple handling.

These circular saws meet all requirements due to their fully galvanised and powder-coated all-steel design.

The chassis with its handhold and a full rubber wheel makes an easy transport possible.

*An economic solution
for working with fire-
wood!*

Types overview

Technical information



Wisa 700Z

Design model	Tilting circular saw Wisa 700Z	Tilting circular saw Wisa 700ZMG
Type	Fully galvanised and powder-coated all-steel design	Fully galvanised and powder-coated all-steel design
Saw blade	Ø 700mm	Ø 700mm
Cutting depth	300 mm	300 mm
Drive	PTO with slipping clutch	Combined drive electric engine (5,5 kW) and PTO-drive (8,0 kW)
Electricity		switch-plug-combination 16 A with phase inverter (400V)
Weight	110 kg	140 kg
Further details	Angular gear, steel muff, for tractors over 15 HP	Special circular saw engine with overheating protection, extraordinary strong grey cast iron case, electronic engine brake

Type overview design model Wisa 700Z

Saw blade	Gear	Slipping clutch	Item num.
700 CS-KV	540 rpm	Included	31.330

Type overview design model Wisa 700ZMG

Saw blade	Gear	Slipping clutch	Item num.
700 CS-KV	540 rpm	5,5 KW; 400 Volt/16 Ampere, 5-pole	31.525
700 CS-KV	540 rpm	8,0 KW; 400 Volt/16 Ampere, 5-pole	31.560



Wisa 700ZMG

Accessories

Accessories	Item num.
Joint shaft	14.692
Off-road wheel, galvanised/powder-coated	39.003
Chassis with two wheels and a lift handle	39.005
Tilt extension left	39.020
Tilt extension right	39.022
HM – saw blade	42.108



Technical and optical alterations are possible